



ITEM	NAME OF PART	MATERIAL	NOTES
5	Clamp	Copper alloy	Sn plated
4	Cage	Copper alloy	M3/Ni plated
3	Screw	Steel	M3/Zn plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准 / UL Standard:	B	C	D
额定电压/电流 / Rated Voltage(V)/Current(A)	300/15	/	300/10
EC 标准 / EC Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	III/2		
额定电压/电流 / Rated Voltage(V)/Current(A)	320/20		
额定脉冲电压 (KV) / Rate Impulse Voltage (KV)	4.0		
额定扭矩 / Torque Tightening (N·m/Lb.in)	M3 0.5/4.43		
线径范围 (硬线和软线) / Wire Range (rigid and flexible) (mm <sup>2</sup> / AWG)	1.0~2.5 / 28~12		
间距 / Pitch (mm) / 线数范围 / Poles	5.08 / N=02~24P		
绝缘长度 / Stripping length (mm)	7-8		
使用温度范围 / Operating temperature (°C)	-40~+105		
符合RoHS环保要求 / Conform to RoHS	Yes		
标准颜色编号 / Standard color number:	/		
PANTONE / RAL	/		

MATERIAL: SURFACE:

MAT NO.:  
STATUS:  
APPD:  
CHKD:  
DRT:

NAME: **宁波三安电子科技有限公司**  
Sanan Electrical Technology Co. Ltd

DRAWING NO.: **ZESAK-5.08-XXP-1Y-1000A&Z(H)**

TYPE: SCALE: SHEET 1/1

公差 (General)	tolerances (mm)
0	>3
~	>6
~	>10
~	>18
~	>30
~	>50
~	>80
~	>120
~	>180
~	>250
~	>315
~	>400
~	>500
~	>500

